LIMENTE



ZIRCON 680

aluminium | 8 W | 460 lm Product code: 626483

An easy-to-install, connectable light fixture

LIMENTE ZIRCON profile light fixtures are installed one after another with connectors integrated in the fixtures. As a result, you'll have a profile light fixture providing constant, even, and efficient working light on a counter top. Both bright and matte diffusers are included in delivery. The light is softer and the led points are less visible when using the matte diffuser.

Choose the right number of fixtures by counting the total length of the fixtures. Also note the space that the power supply cord and the light switch (123mm) take up. You'll also need a 12V power supply (no. LED26050, max. 50W). There is a switch/dimmer available for LIMENTE ZIRCON. Both have the same design. The switch is placed between the power supply and first of the fixtures.

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE ZIRCON with the dimmer in our ZIRCON products (no. 621584). You can choose between three different settings in the amount of light provided: 100% - 60% - 20%.

Additional light fixtures

You can easily extend your ZIRCON lighting design by adding up to 5 light fixtures to the ZIRCON power supply (no. LED26050). The fixtures can be any LIMENTE light fixtures at the voltage of 12V that have a white (12V) TOP connector. Please note the adequate length of the cord and the maximum load (W) of the power supply.

THE FOLLOWING ITEMS ARE INCLUDED



ZIRCON 680 8,0 W AL

OVERVIEW

| PRODUCT CODE | 626483 |
|-------------------|------------------------------------|
| GTIN-CODE | 6430022827806 |
| ELECTRICAL NUMBER | 4118848 |
| ETIM GENERAL NAME | |
| ETIM CLASS | Light ribbon-/hose/-strip EC002706 |
| ETIM GROUP | |
| COLOUR | Alulook |
| LAMP TYPE | LED |

SPECIFICATIONS

| PRODUCT DIMENSIONS | 680.0 x 30.0 x 10.0 |
|-----------------------------------|---|
| MOUNTING METHOD | Surface mounting |
| COLOUR TEMPERATURE | 4000 K |
| COLOUR RENDERING INDEX CRI | > 80 |
| RATED LIFE TIME | |
| ENERGY EFFICIENCY CLASS | |
| LUMINOUS FLUX | 460 lm |
| EFFICIENCY | 58 lm/W |
| VOLTAGE | 12 V DC |
| INGRESS PROTECTION CODE | IP20 |
| NUMBER OF LEDS/M | |
| INPUT POWER | 8,0 W |
| NUMBER OF SWITCHING CYCLES | > 50 000 |
| AMBIENT TEMPERATURE RANGE | |
| INPUT POWER CONNECTOR | Amp, hole diameter 15 mm |
| WARRANTY PERIOD (MONTHS) | 24 |
| ADDITIONAL COVER (MONTHS) | - |
| INSTALLATION AND OPERATING MANUAL | http://www.lapetek.fi//tuotekuvat/ao/limente_led-zircon.pdf |

Date: 19.02.2025 | Page 2 (3)



ZIRCON 680 8,0 W AL

RECOMMENDED ACCESSORIES

| PRODUCT CODE | PRODUCT |
|--------------|--|
| LED26015 | LIMENTE DRIVER, WHITE, 12 V, 0-15 W (6XTOP) |
| LED26030 | LIMENTE DRIVER, WHITE, 12 V, 0-30 W (6XTOP) |
| LED26050 | LIMENTE DRIVER, WHITE, 12 V, 0-50 W (10XTOP) |
| 640410 | SMART 410, WIRELESS LIGHTCONTROL |
| 640421 | SMART 421, WIRELESS LIGHT CONTROL |
| 640422 | SMART 422, WIRELESS LIGHT CONTROL |

Date: 19.02.2025 | Page 3 (3)