

ZIRCON 1020

aluminium | 11,2 W | 690 lm

Product code: 626583

An easy-to-install, connectable light fixture

LIMENTE ZIRCON profile light fixtures are installed one after another with connectors integrated in the fixtures. As a result, you'll have a profile light fixture providing constant, even, and efficient working light on a counter top. Both bright and matte diffusers are included in delivery. The light is softer and the led points are less visible when using the matte diffuser.

Choose the right number of fixtures by counting the total length of the fixtures. Also note the space that the power supply cord and the light switch (123mm) take up. You'll also need a 12V power supply (no. LED26050, max. 50W). There is a switch/dimmer available for LIMENTE ZIRCON. Both have the same design. The switch is placed between the power supply and first of the fixtures.

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE ZIRCON with the dimmer in our ZIRCON products (no. 621584). You can choose between three different settings in the amount of light provided: 100% - 60% - 20%.

Additional light fixtures

You can easily extend your ZIRCON lighting design by adding up to 5 light fixtures to the ZIRCON power supply (no. LED26050). The fixtures can be any LIMENTE light fixtures at the voltage of 12V that have a white (12V) TOP connector. Please note the adequate length of the cord and the maximum load (W) of the power supply.

THE FOLLOWING ITEMS ARE INCLUDED

ZIRCON 1020 11,2 W AL

OVERVIEW

PRODUCT CODE	626583
GTIN-CODE	6430022827813
ELECTRICAL NUMBER	4118849
ETIM GENERAL NAME	
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	
COLOUR	Alulook
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	1020.0 x 30.0 x 10.0
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 80
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	690 lm
EFFICIENCY	62 lm/W
VOLTAGE	12 V DC
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	
INPUT POWER	11,2 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	
INPUT POWER CONNECTOR	Amp, hole diameter 15 mm
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	-
INSTALLATION AND OPERATING MANUAL	http://www.lapetek.fi//tuotekuvat/ao/limente_led-zircon.pdf

ZIRCON 1020 11,2 W AL

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED26015	LIMENTE DRIVER, WHITE, 12 V, 0-15 W (6XTOP)
LED26030	LIMENTE DRIVER, WHITE, 12 V, 0-30 W (6XTOP)
LED26050	LIMENTE DRIVER, WHITE, 12 V, 0-50 W (10XTOP)
640410	SMART 410, WIRELESS LIGHTCONTROL
640421	SMART 421, WIRELESS LIGHT CONTROL
640422	SMART 422, WIRELESS LIGHT CONTROL