

LED-SLIM

3000 K | aluminium | 13,8 W | 1500 lm/m

Product code: 629353



An extendable profile fixture

LIMENTE LED-SLIM is a versatile lighting system that allows you to custom design and build your own lighting system. The fixture is available in color temperatures of 3000K and 4000K and allows you to build unified lighting, where corners are also illuminated. The LED-SLIM is well suited for a kitchen workspace, a showcase, inside a wardrobe, for store shelves and any space, where stylish, uniform and efficient lighting is desired. The LIMENTE LED-SLIM system is available in sections of 10, 20, 30, 50 and 100 cm lengths. Don't forget the 90-degree corner pieces and the flexible corner pieces available!

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE LED-SLIM 3000K with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

Installation

The system is simple to design and implement by following the instructions below.

[Learn more from our website](#)



THE FOLLOWING ITEMS ARE INCLUDED

- profil lamp

SLIM 50 13,8W 3K AL PROF.LIGHT

OVERVIEW

PRODUCT CODE	629353
GTIN-CODE	6430022820210
ELECTRICAL NUMBER	4118942
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	Alulook
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	511.0 x 30.0 x 12.0
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX CRI	> 80
RATED LIFE TIME	35.000h (L80B10)
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	750 lm
EFFICIENCY	53 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP21
NUMBER OF LEDS/M	
INPUT POWER	13,8 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	Läpjojhdotettu
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-slim.pdf

SLIM 50 13,8W 3K AL PROF.LIGHT

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LED POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LED POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LED POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640420	SMART 420, WIRELESS LIGHT CONTROL
640421	SMART 421, WIRELESS LIGHT CONTROL
640422	SMART 422, WIRELESS LIGHT CONTROL
640424	SMART 422, WIRELESS LIGHT CONTROL
640425	SMART 425, WIRELESS LIGHT CONTROL

SLIM 50 13,8W 3K AL PROF.LIGHT

