



PROFILE NEONMINI

without led-strip | aluminum 2 x 1,0 m

Product code: 630011

NEONMINI-35 profile – discreet ambient lighting

The NEONMINI aluminum profile is specifically designed for the installation of the NEONMINI-35 strip. This ultra-compact and discreet profile allows for a clean surface-mounted installation of the strip, while ensuring a seamless finish when the luminaire is intended to be recessed into the interior, making it nearly invisible.

The profile is an excellent choice for grooves made in the sides of closets, furniture, and for ambient lighting in toe kicks and countertops—as well as anywhere you want the light source to remain hidden from view.

Adjusting the lighting

The LIMENTE NeonMini is dimmable with the LIMENTE SMART 512 IR door switch. LIMENTE SMART 512 IR door switch acts as an automatic door ON / OFF switch or when used as a door switch, the switch turns on the lights when the door is opened and turns them off when the door is closed.

[Learn more from our website](#)

Installation

NEONMINI profiles are cut to the desired length using a hacksaw or a circular saw, after which the profile is fixed in place using either screws or adhesive. The NEONMINI-35 strip (ordered separately) completes the installation when it is pressed firmly into the profile. Using the profile ensures a perfectly straight and stylish result, which would not be possible with individual clips alone. Please note that the profile is delivered without clips or screws, so please choose the mounting method best suited for your installation site separately.

THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profiles 2 x 1m
- diffuser 2 x 1m (cover)
- mounting clips screws 4 pcs
- end-caps 4 pcs

PROFILE NEONMINI 2 X 1M AL

OVERVIEW

PRODUCT CODE	630011
GTIN-CODE	6430022827592
ELECTRICAL NUMBER	4158097
ETIM GENERAL NAME	
ETIM CLASS	
ETIM GROUP	
COLOUR	
LAMP TYPE	

SPECIFICATIONS

PRODUCT DIMENSIONS	1000.0 x 6.0 x 4.8
MOUNTING METHOD	
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	
INGRESS PROTECTION CODE	
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_neonmini.pdf

PROFILE NEONMINI 2 X 1M AL

