



ELITE

socket | aluminum/s/s

Product code: 630501

Recessed tabletop socket

ELITE is a stylish socket that is suitable for many different areas such as kitchen, offices and workstations. Socket outlets are normally hidden beneath the mounting surface. When the sockets are needed, the socket tower is raised on top of the surface. After use, the outlet port is pressed back down.

The product includes slots for three socket and a two-meter power supply cord. ELITE can be mounted as well in vertical as horizontal position.

Color options

ELITE is available in aluminum/s/s and chrome/chrome.

Installation

ELITE socket is simple and quick to install. A hole with a diameter of 100 mm or 124 mm is made to the mounting surface, where the socket is tightened with a nut. The 100mm hole is for installation without a flush mounting adapter, in which case the socket comes in the closed position 10mm above the level. The 124mm hole is for installation with a flush-mounting adapter, in which case the socket comes in the closed position 1.5mm above the level. The electrical connection is made using the supplied 2 m power cord. Please note that within a distance of up to two meters should be an earthed socket and that the socket requires a mounting depth of 20 cm. The power consumption of the USB ports in Elite sockets in standby mode is <0.3W. Installation does not require an electrician.

THE FOLLOWING ITEMS ARE INCLUDED

- socket with 2m supply cable
- grounded plug
- separate flush-mounted adapter that enables installation in a hole with a diameter of 100 mm and 124 mm

ELITE SOCKET ALUMINUM/S/S

OVERVIEW

PRODUCT CODE	630501
GTIN-CODE	8028067013711
ELECTRICAL NUMBER	2509109
ETIM GENERAL NAME	Socket
ETIM CLASS	Socket outlet EC000125
ETIM GROUP	25 Flush sockets
COLOUR	
LAMP TYPE	

SPECIFICATIONS

PRODUCT DIMENSIONS	364.0 x 120.0 x 120.0
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	240 V
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	+5°C - +40°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	http://www.limente.fi/Images/productpics/instructions/Limente_Elite.pdf

ELITE SOCKET ALUMINUM/S/S

