LIMENTE



TOWER-3

socket |

Product code: 63171

A recessed power socket

The Tower-3 is a stylish socket that is suitable for many different areas such as kitchen, offices and workstations. Socket outlets are normally hidden beneath the mounting surface. When the sockets are needed, the socket tower is raised on top of the surface. After use, the outlet port is pressed back down.

The product includes slots for three socket and a two-meter power supply cord. The TOWER-3 can be mounted as well in vertical as horizontal position.

Color options

Tower-3 is available in aluminium/black or chrome.

Installation

The Tower socket is simple and quick to install. A 80 mm hole is made to the mounting surface, where the socket is tightened with a nut. The electrical connection is made using the supplied 2 m power cord. Please note that within a distance of up to two meters should be an earthed socket and that the socket requires a mounting depth of 20 cm. Installation does not require an electrician.

THE FOLLOWING ITEMS ARE INCLUDED

- socket with 2m supply cable
- grounded plug

Date: 13.03.2024 | Page 1 (3



TOWER-3 SOCKET AL

OVERVIEW

PRODUCT CODE	63171
GTIN-CODE	6430022829978
ELECTRICAL NUMBER	2407113
ETIM GENERAL NAME	Socket
ETIM CLASS	Socket outlet EC000125
ETIM GROUP	24 Surface mounting socket-outlets and plugs
COLOUR	Alulook
LAMP TYPE	-

SPECIFICATIONS

PRODUCT DIMENSIONS	217.0 x 111.0 x 111.0
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	240 V
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	
INPUT POWER	-
NUMBER OF SWITCHING CYCLES	-
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	http://www.limente.fi/Images/productpics/instructions/Limente_tower-3.pdf

Date: 13.03.2024 | Page 2 (3)

LIMENTE

TOWER-3 SOCKET AL



