



## LIFT

socket | s/s

Product code: 63311

### A recessed power socket

LIFT is a stylish tower socket that is suitable for use in many different places, such as kitchens, offices, and workstations. Thanks to its compact size and minimalist design, it is very user-friendly and fits into all kinds of environments, both modern and classic.

The LIFT tower socket opens and closes with a soft and quiet motion, enhancing user comfort. Its refined appearance exudes quality and durability. Thanks to its protective cover, the socket is splash-proof (IP 54) when closed.

[Learn more from our website](#)

### Color options

The socket cover is available in the same color tones as the Desk-2 and Mono recess mounted sockets: stainless steel, brushed black, brushed gold, copper, tin, black glass, and white glass. For models with a wireless charger, the cover is either white or black.

### Installation

The LIFT tower socket is quick and easy to install.

[Learn more from our website](#)

#### THE FOLLOWING ITEMS ARE INCLUDED

- socket with 2m supply cable
- grounded plug
- 2 x Schuko + USB A/C

## LIFT SQ S/S USB

## OVERVIEW

|                   |                        |
|-------------------|------------------------|
| PRODUCT CODE      | 63311                  |
| GTIN-CODE         | 8028067155749          |
| ELECTRICAL NUMBER | 2509310                |
| ETIM GENERAL NAME | Socket                 |
| ETIM CLASS        | Socket outlet EC000125 |
| ETIM GROUP        | 25 Flush sockets       |
| COLOUR            |                        |
| LAMP TYPE         |                        |

## SPECIFICATIONS

|                                   |   |
|-----------------------------------|---|
| PRODUCT DIMENSIONS                | 305.0 x 80.0 x 150.0  |
| MOUNTING METHOD                   | Flush mounting  |
| COLOUR TEMPERATURE                |   |
| COLOUR RENDERING INDEX CRI        |   |
| RATED LIFE TIME                   |   |
| ENERGY EFFICIENCY CLASS           |   |
| LUMINOUS FLUX                     |   |
| EFFICIENCY                        |   |
| VOLTAGE                           | 240 V   |
| INGRESS PROTECTION CODE           | IP54  |
| NUMBER OF LEDS/M                  |   |
| INPUT POWER                       |   |
| NUMBER OF SWITCHING CYCLES        |   |
| AMBIENT TEMPERATURE RANGE         | -20°C~35°C  |
| INPUT POWER CONNECTOR             |   |
| WARRANTY PERIOD (MONTHS)          | 24  |
| ADDITIONAL COVER (MONTHS)         |   |
| INSTALLATION AND OPERATING MANUAL | <a href="https://www.limente.fi/Images/productpics/instructions/Limente_Lift.pdf">https://www.limente.fi/Images/productpics/instructions/Limente_Lift.pdf</a> |

## LIFT SQ S/S USB

### RECOMMENDED ACCESSORIES

| PRODUCT CODE | PRODUCT          |
|--------------|------------------|
| 680826       | LIFT, CARTER KIT |

## LIFT SQ S/S USB

