

RIBBON 40 COM

24 V | 4000 K | IP44 | 192 led/m | 1512 lm/m | CRI>85
Product code: 682327



4000 K



THE FOLLOWING ITEMS ARE INCLUDED

- ribbon, with in both ends driver
- 2 x 3m power cord with TOP connector

A versatile LED strip

LIMENTE RIBBON IP44 B is an efficient led strip with LEDs very close to each other (180 LEDs / m). You can use RIBBON either in a kitchen as working light or as indirect light behind mirrors, in plinths, in ceilings, and in any space. where the light source needs to be as invisible as possible. LIMENTE RIBBON can be shortened to a desired length at 3,3 cm intervals. The light is stylish and continuous as well as pleasantly even especially when installed on LIMENTE LIGHT PROFILE.

LIMENTE RIBBON IP44 B comes with quality LEDs with a color rendering index of Ra> 85, an efficiency of 80 lm/W, a luminosity of 1080lm/m and a color temperature of about 4000K (small color temperature differences may vary by production batches).

[Learn more from our website](#)

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE RIBBON IP44 B with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

Installation

LIMENTE RIBBON IP44 B is fast and easy to install.

[Learn more from our website](#)

RIBBON 40 COM 4K IP44 STRIP

OVERVIEW

PRODUCT CODE	682327
GTIN-CODE	6438400000537
ELECTRICAL NUMBER	4129644
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	White
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	4000.0 x 10.0 x 3.0
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 85
RATED LIFE TIME	36.000h (L80B10), 84.000h (L70B50)
ENERGY EFFICIENCY CLASS	G
LUMINOUS FLUX	1512 lm/m
EFFICIENCY	126 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44
NUMBER OF LEDS/M	192
INPUT POWER	48 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	Top, hole Ø 8 mm
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_ribbon-pro.pdf

RIBBON 40 COM 4K IP44 STRIP

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
682300	PROFILE LINEA, WITHOUT LED-STRIP, ALUMINUM 2,0 M + 1,0 M
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS

RIBBON 40 COM 4K IP44 STRIP

