LIMENTE



24 V | 4000 K

RIBBON 25

24 V | 4000 K | IP20 | 180 led/m | 1200 lm/m | CRI>80 Product code: 682333

A versatile LED strip

LIMENTE RIBBON IP20 is an efficient led strip with LEDs very close to each other (180 LEDs / m). You can use RIBBON either in a kitchen as working light or as indirect light behind mirrors, in plinths, in ceilings, and in any space. where the light source needs to be as invisible as possible. LIMENTE RIBBON can be shortened to a desired length at 3,3 cm intervals. The light is stylish and continuous as well as pleasantly even especially when installed on LIMENTE LIGHT PROFILE.

LIMENTE RIBBON IP20 led strip is available in standard lengths of 2,5 and 6 meters. The strip can be shortened to a desired length at 3,3 cm intervals. LIMENTE RIBBON IP20 comes with quality LEDs with a color rendering index of Ra> 80, an efficiency of 85 lm/W, a luminosity of 1200lm/m and a color temperature of about 3000K or 4000K.

Learn more from our website

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE RIBBON IP20 with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

Learn more from our website

Installation

LIMENTE RIBBON IP20 is fast and easy to install. Learn more from our website

THE FOLLOWING ITEMS ARE INCLUDED

- ribbon, with in both ends driver
- 2 x 3m power cord with TOP connector



RIBBON 25 4K IP20 STRIP

OVERVIEW

PRODUCT CODE	682333
GTIN-CODE	6438400001701
ELECTRICAL NUMBER	4129702
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	White
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	2500.0 x 10.0 x 2.0
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 80
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	1200 lm/m
EFFICIENCY	90 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	180
INPUT POWER	36 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C -+50°C
INPUT POWER CONNECTOR	Top, hole Ø 8 mm
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-ribbon.pdf

Date: 05.05.2025 | Page 2 (4)



RIBBON 25 4K IP20 STRIP

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
640420	SMART 420, WIRELESS LIGHT CONTROL
640421	SMART 421, WIRELESS LIGHT CONTROL
640422	SMART 422, WIRELESS LIGHT CONTROL
640424	SMART 422, WIRELESS LIGHT CONTROL
640425	SMART 425, WIRELESS LIGHT CONTROL

Date: 05.05.2025 | Page 3 (4)



RIBBON 25 4K IP20 STRIP

