


## LILA 20

2m | 4000 K | aluminum | 140 led/m | 1300 lm/m | CRI>80  
Product code: 682352



### A versatile recessed profile fixture

LIMENTE LILA is a profile fixture for indirect lighting, which is especially pleasant when planning on illuminating via another surface. The fixture can be used e.g. in closets, when wanting to direct light toward the back wall of the closet. LILA is a recessed profile fixture, which is submerged into a surface. The profile is very small in size and, unlike other LIMENTE-profiles, LILA and LILO use an 8mm led strip.

LILA is a versatile fixture for working light and mood light. The fixture can be shortened to a desired length. The light is stylish and continuous with no connection points interrupting the light, which provides even light throughout the area.

[Learn more from our website](#)

### Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE LILA with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

### Easy installation

LIMENTE LILA is fast and easy to install with the installation tools included.

[Learn more from our website](#)



### THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m
- end pieces x 8
- led-ribbon 2 m, with driver in both ends
- 3m power cords 2 pcs

## LILA 20 4K AL PROFILE LIGHT

## OVERVIEW

PRODUCT CODE	682352
GTIN-CODE	6438400001961
ELECTRICAL NUMBER	4129724
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	Alulook
LAMP TYPE	LED

## SPECIFICATIONS

PRODUCT DIMENSIONS	2000.0 x 24.0 x 10.5
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 80
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	1300 lm/m
EFFICIENCY	
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	140
INPUT POWER	20 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	<a href="https://www.limente.fi/Images/productpics/instructions/limente_led-lila.pdf">https://www.limente.fi/Images/productpics/instructions/limente_led-lila.pdf</a>

## LILA 20 4K AL PROFILE LIGHT

## RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640551	SMART 551, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640552	SMART 552, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640554	SMART 554, LUXUS LIGHTCONTROL KIT, 24 V, BLACK
640556	SMART 556, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640557	SMART 557, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640425	SMART 425, WIRELESS LIGHT CONTROL

## LILA 20 4K AL PROFILE LIGHT

