

LILO 20

2m | 3000 K | aluminum | 140 led/m | 1300 lm/m | CRI>80
Product code: 682354



A versatile surface-mounted profile fixture

LIMENTE LILLO is a profile fixture for indirect lighting, which is especially pleasant when planning on illuminating via another surface. The fixture can be used e.g. in closets, when wanting to direct light toward the back wall of the closet. LILLO is a surface-mounted profile fixture. The profile is very small in size and, unlike other LIMENTE-profiles, LILA and LILLO use an 8mm led strip.

LILLO is a versatile fixture for working light and mood light. The fixture can be shortened to a desired length. The light is stylish and continuous with no connection points interrupting the light, which provides even light throughout the area.

[Learn more from our website](#)

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE LILLO with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

Easy installation

LIMENTE LILLO is fast and easy to install with the installation tools included.

[Learn more from our website](#)



THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m
- end pieces x 4
- fasteners x 4
- led-ribbon 2 m, with driver in both ends
- 3m power cords 2 pcs

LILO 20 3K AL PROFILE LIGHT

OVERVIEW

| | |
|-------------------|------------------------------------|
| PRODUCT CODE | 682354 |
| GTIN-CODE | 6438400001985 |
| ELECTRICAL NUMBER | 4129726 |
| ETIM GENERAL NAME | Light ribbon-/hose/-strip |
| ETIM CLASS | Light ribbon-/hose/-strip EC002706 |
| ETIM GROUP | 41 Domestic light fittings |
| COLOUR | Alulook |
| LAMP TYPE | LED |

SPECIFICATIONS

| | |
|-----------------------------------|---|
| PRODUCT DIMENSIONS | 2000.0 x 22.6 x 10.5 |
| MOUNTING METHOD | Surface mounting |
| COLOUR TEMPERATURE | 3000 K |
| COLOUR RENDERING INDEX CRI | > 80 |
| RATED LIFE TIME | 54.000h (L80B10), 102.000h (L70B50) |
| ENERGY EFFICIENCY CLASS | |
| LUMINOUS FLUX | 1300 lm/m |
| EFFICIENCY | |
| VOLTAGE | 24 V DC |
| INGRESS PROTECTION CODE | IP20 |
| NUMBER OF LEDS/M | 140 |
| INPUT POWER | 20 W |
| NUMBER OF SWITCHING CYCLES | > 50 000 |
| AMBIENT TEMPERATURE RANGE | -20°C~50°C |
| INPUT POWER CONNECTOR | |
| WARRANTY PERIOD (MONTHS) | 24 |
| ADDITIONAL COVER (MONTHS) | 12 |
| INSTALLATION AND OPERATING MANUAL | https://www.limente.fi/Images/productpics/instructions/limente_led-lilo.pdf |

LILO 20 3K AL PROFILE LIGHT

RECOMMENDED ACCESSORIES

| PRODUCT CODE | PRODUCT |
|--------------|--|
| LED28030 | LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS |
| LED28060 | LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS |
| LED28100 | LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS |
| 640420 | SMART 420, WIRELESS LIGHT CONTROL |
| 640421 | SMART 421, WIRELESS LIGHT CONTROL |
| 640422 | SMART 422, WIRELESS LIGHT CONTROL |
| 640424 | SMART 422, WIRELESS LIGHT CONTROL |
| 640425 | SMART 425, WIRELESS LIGHT CONTROL |

LILO 20 3K AL PROFILE LIGHT

