LIMENTE



4000 K



THE FOLLOWING ITEMS ARE INCLUDED

- ribbon, with in both ends driver
- 2 x 3m power cord with TOP connector

RIBBON 20 8

24 V | 4000 K | IP20 | 140 led/m | 1300 lm/m | CRI>80 Product code: 682360

A versatile LED strip

LIMENTE RIBBON IP20 8 is an efficient led strip with LEDs very close to each other (140 LEDs / m). You can use RIBBON either in a kitchen as working light or as indirect light behind mirrors, in plinths, in ceilings, and in any space. where the light source needs to be as invisible as possible. The light is stylish and continuous as well as pleasantly even especially when installed on LIMENTE LIGHT PROFILE.

LIMENTE RIBBON IP20 8 led strip is available in standard lengths of 2 and 4 meters. The strip can be shortened to a desired length at about 5cm intervals. LIMENTE RIBBON IP20-8 comes with quality LEDs with a color rendering index of Ra>80, an efficiency of 130 lm/W, a luminosity of 1300lm/m and a color temperature of about 3000K or 4000K.

Learn more from our website

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE RIBBON IP20 with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

Learn more from our website

Installation

LIMENTE RIBBON IP20 8 is fast and easy to install.

Learn more from our website



RIBBON 20 8 4K IP20 STRIP

OVERVIEW

682360
6438400002043
4129732
Light ribbon-/hose/-strip
Light ribbon-/hose/-strip EC002706
41 Indoor luminares
White
LED

SPECIFICATIONS

PRODUCT DIMENSIONS	2000.0 x 8.0 x 1.3
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 80
RATED LIFE TIME	102.000h
ENERGY EFFICIENCY CLASS	E
LUMINOUS FLUX	1300 lm/m
EFFICIENCY	130 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	140
INPUT POWER	20 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C -+50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_ribbon-pro.pdf

Date: 04.07.2025 | Page 2 (4)



RIBBON 20 8 4K IP20 STRIP

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640552	SMART 552, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640554	SMART 554, LUXUS LIGHTCONTROL KIT, 24 V, BLACK
640556	SMART 556, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640557	SMART 557, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640551	SMART 551, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640425	SMART 425, WIRELESS LIGHT CONTROL

Date: 04.07.2025 | Page 3 (4)

LIMENTE

RIBBON 20 8 4K IP20 STRIP



