

## DUO 40 CCT

4m | 2700 - 6000 K | white | IP44 | 2x1500 lm/m | CRI>90  
Product code: 682364



### An up & down wall light fixture with color temperature adjustment

LIMENTE DUO IP44 CCT is a minimalistic and sleek wall light profile fixture that projects light up and down. The fixture is available in both black and white. DUO can be used in private homes and in public spaces as an eye-catcher, a mood light or a functional light for reading or above a couch.

You can control both the upward projecting light and the downward projecting light separately when needed. Using DUO enables carrying out beautiful and stylish indirect lighting designs in different kinds of spaces, including in the bathroom due to the fixtures IP44 classification.

[Learn more from our website](#)

### Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE DUO IP44 CCT with our wireless system. You can use the same switch to adjust all the LIMENTE CCT lights in the room. The light and color temperature adjust smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

### Easy installation

LIMENTE DUO IP44 CCT is fast and easy to install. Simply fasten the attachment board to the desired place with screws and attach the fixture by pressing it onto the attachment board.

[Learn more from our website](#)



### THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m x 2
- end pieces x 8
- mounting clips x 12
- 2 x led-ribbon 4 m, with 1,5 m power cord in both ends
- 1,5 m power cords 2 pcs

## DUO 40 CCT LUX WH PROF.LIGHT

## OVERVIEW

PRODUCT CODE	682364
GTIN-CODE	6438400002081
ELECTRICAL NUMBER	4129736
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	White
LAMP TYPE	LED

## SPECIFICATIONS

PRODUCT DIMENSIONS	4000.0 x 48.5 x 17.8
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	2700 - 6000 K
COLOUR RENDERING INDEX CRI	> 90
RATED LIFE TIME	120.000h
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	2 x 1500 lm/m
EFFICIENCY	105 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44
NUMBER OF LEDS/M	180
INPUT POWER	2 x 58 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C -+50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	<a href="https://www.limente.fi/Images/productpics/instructions/limente_led-duo.pdf">https://www.limente.fi/Images/productpics/instructions/limente_led-duo.pdf</a>

## DUO 40 CCT LUX WH PROF.LIGHT

## RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640560	SMART 560, CCT RECEIVER, CCT 24 V
640561	SMART 561, LUXUS CCT-CONTROL, 24 V, WHITE
640562	SMART 562, GREENLINE CCT-CONTROL, 24 V, WHITE
640563	SMART 563, LUXUS CCT-CONTROL, 24 V, BLACK

## DUO 40 CCT LUX WH PROF.LIGHT

