


UP 20

2m | 4000K | white | 192 led/m | 1512 lm/m | CRI>85

Product code: 682384



A stylish profile fixture for indirect light

LIMENTE UP IP44 B is a minimalistic and sleek wall light profile fixture that projects light up or down, depending on how the fixture is installed. The fixture is available in both black and white. LIMENTE UP is an excellent choice for both in residential and commercial projects or offices for indirect lighting. The fixture enables carrying out beautiful and stylish indirect lighting designs in different kinds of spaces.

UP is a surface-mounted light fixture, which means the only thing to take into consideration when installing is how to bring the power supply cord to the fixture. The led strip can be shortened to a desired length at 3,3 cm intervals, whereas the profile has a standard length of 2m and can be shortened to a desired length.

[Learn more from our website](#)

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE UP IP44 B with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

[Learn more from our website](#)

Installation

LIMENTE UP IP44 B is fast and easy to install with the installation tools included.

[Learn more from our website](#)



THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m
- end pieces x 4
- fasteners x 6
- led-ribbon 2 m, with driver in both ends
- 3m power cords 2 pcs

UP 20 COM 24W 4000K WH

OVERVIEW

PRODUCT CODE	682384
GTIN-CODE	6438400002289
ELECTRICAL NUMBER	4129756
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Indoor luminaires
COLOUR	White
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	2000.0 x 43.5 x 17.8
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 85
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	1512 lm/m
EFFICIENCY	126 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44
NUMBER OF LEDS/M	180
INPUT POWER	24 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C -+50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	12
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-up.pdf

UP 20 COM 24W 4000K WH

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640552	SMART 552, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640554	SMART 554, LUXUS LIGHTCONTROL KIT, 24 V, BLACK
640556	SMART 556, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640557	SMART 557, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640425	SMART 425, WIRELESS LIGHT CONTROL

UP 20 COM 24W 4000K WH

