LIMENTE



LINEA LUX

2m | 3000 K | black | 192 led/m | 1700 lm/m | CRI>90 Product code: 682390

A versatile light profile fixture

LIMENTE LINEA IP44 LUX is a part of LIMENTE LUX collection. The LIMENTE LUX collection provides the best quality of light in technical features, such as efficiency and color rendering, and maximizes the lifespan of the product. LIMENTE LINEA IP44 LUX is a versatile light fixture suitable for either working light or mood light. The fixture can be used in kitchen workspace but also to provide indirect lighting when placed above upper cabinets, in plinths, in ceilings or inside a wardrobe or any other space, where light is needed.

See "Installation pictures" for tips on how to use LINEA IP44 LUX as working lighting in a kitchen workspace but also as indirect lighting when placed above upper cabinets or inside a wardrobe! In kitchen workspaces the fixture is installed near the front edge of the kitchen upper cabinet. LIMENTE LINEA profile fixtures are available in multiple lengths (2-6m) and three different color temperatures (3000K, 4000K and 2700K-6000K). The profile itself has a standard length of 2m and can be shortened to a desired length.

Learn more from our website

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE LINEA IP44 LUX with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

Learn more from our website

Easy installation

LIMENTE LINEA IP44 LUX is fast and easy to install with the installation tools included.

Learn more from our website

THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m
- end caps x 4
- mounting clips x 7
- plastic corner pieces (90°) x 3
- led-ribbon 2 m, driver in both ends
- 3m power cords 2 pcs



LINEA 20 LUX 3K AL PROF.LIGHT

OVERVIEW

| PRODUCT CODE | 682390 |
|-------------------|------------------------------------|
| GTIN-CODE | 6438400005372 |
| ELECTRICAL NUMBER | 4139936 |
| ETIM GENERAL NAME | Light ribbon-/hose/-strip |
| ETIM CLASS | Light ribbon-/hose/-strip EC002706 |
| ETIM GROUP | 41 Domestic light fittings |
| COLOUR | Black |
| LAMP TYPE | LED |

SPECIFICATIONS

| PRODUCT DIMENSIONS | 2000.0 x 17.0 x 8.0 |
|-----------------------------------|--|
| MOUNTING METHOD | Surface mounting |
| COLOUR TEMPERATURE | 3000 K |
| COLOUR RENDERING INDEX CRI | > 90 |
| RATED LIFE TIME | |
| ENERGY EFFICIENCY CLASS | |
| LUMINOUS FLUX | 1700 lm/m |
| EFFICIENCY | 130/135 lm/W |
| VOLTAGE | 24 V DC |
| INGRESS PROTECTION CODE | IP44 |
| NUMBER OF LEDS/M | 180 |
| INPUT POWER | 28 W |
| NUMBER OF SWITCHING CYCLES | > 50 000 |
| AMBIENT TEMPERATURE RANGE | -20°C~50°C |
| INPUT POWER CONNECTOR | |
| WARRANTY PERIOD (MONTHS) | 24 |
| ADDITIONAL COVER (MONTHS) | 36 |
| INSTALLATION AND OPERATING MANUAL | https://www.limente.fi/Images/productpics/instructions/limente_led-linea.pdf |



LINEA 20 LUX 3K AL PROF.LIGHT

RECOMMENDED ACCESSORIES

| PRODUCT CODE | PRODUCT |
|--------------|--|
| LED28030 | LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS |
| LED28060 | LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS |
| LED28100 | LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS |
| 640551 | SMART 551, LUXUS LIGHTCONTROL KIT, 24 V, WHITE |
| 640552 | SMART 552, LUXUS LIGHTCONTROL KIT, 24 V, WHITE |
| 640554 | SMART 554, LUXUS LIGHTCONTROL KIT, 24 V, BLACK |
| 640556 | SMART 556, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE |
| 640557 | SMART 557, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE |
| 640425 | SMART 425, WIRELESS LIGHT CONTROL |

Date: 06.05.2024 | Page 3 (4)

LIMENTE

LINEA 20 LUX 3K AL PROF.LIGHT

