LIMENTE



THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2,15 m
- · end pieces x 4
- fasteners x 4
- · led-ribbon 2 m, with driver in both ends
- 3m power cords 2 pcs

CORNER

2,15m | 3000 K | black | 192 led/m | 1380 lm/m | CRI>85 Product code: 682419

A versatile corner profile

LIMENTE CORNER IP44 B is a versatile light fixture suitable for either working light or mood light. The fixture can be used in any space, where the fixture can be placed in a corner. The light is stylish and continuous with no connection points interrupting the light, which provides even light throughout the area.

See "Installation pictures" for tips on how to use CORNER IP44 B in a kitchen workspace but also to provide indirect lighting when placed above upper cabinets, in plinths, in ceilings or inside a wardrobe! LIMENTE CORNER profiles are available in three amazing colors (aluminum, black, white), in multiple lengths (2-6m) and three different color temperatures (3000K, 4000K and 2700K-6000K). The profile itself has a standard length of 2m, black and white 2,15 m and can be shortened to a desired length.

Learn more from our website

Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cosy by dimming your LIMENTE CORNER with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

Learn more from our website

Easy installation

LIMENTE CORNER IP44 B is fast and easy to install with the installation tools included.

Learn more from our website



COR. 20 COM 4K BL PROF.LIGHT

OVERVIEW

PRODUCT CODE	682419
GTIN-CODE	6430022824348
ELECTRICAL NUMBER	4143168
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	Black
LAMP TYPE	LED

SPECIFICATIONS

MOUNTING METHODSurface mountingCOLOUR TEMPERATURE3000 KCOLOUR RENDERING INDEX CRIRATED LIFE TIMEBACOUGH (L80B10), 84.000h (L70B50)ENERGY EFFICIENCY CLASSLUMINOUS FLUX1380 lm/mEFFICIENCY115 lm/WVOLTAGE1844NUMBER OF LEDS/M192INPUT POWER24 WNUMBER OF SWITCHING CYCLES> 50 000AMBIENT TEMPERATURE RANGE-20°C -+50°CINPUT POWER CONNECTOR-20°C -+50°CWARRANTY PERIOD (MONTHS)24ADDITIONAL COVER (MONTHS)12INSTALLATION AND OPERATING MANUALhttps://www.limente.fi/Images/productpics/instructions/limente_led-corner.pdf	PRODUCT DIMENSIONS	2150.0 x 19.0 x 19.0
COLOUR RENDERING INDEX CRI RATED LIFE TIME 36.000h (L80B10), 84.000h (L70B50) ENERGY EFFICIENCY CLASS LUMINOUS FLUX 1380 lm/m EFFICIENCY 115 lm/W VOLTAGE 124 V DC INGRESS PROTECTION CODE IP44 NUMBER OF LEDS/M 192 INPUT POWER AMBIENT TEMPERATURE RANGE IP44 NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	MOUNTING METHOD	Surface mounting
RATED LIFE TIME 36.000h (L80B10), 84.000h (L70B50) ENERGY EFFICIENCY CLASS LUMINOUS FLUX 1380 lm/m EFFICIENCY 115 lm/W VOLTAGE 1P44 NUMBER OF LEDS/M 192 INPUT POWER NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	COLOUR TEMPERATURE	3000 K
ENERGY EFFICIENCY CLASS LUMINOUS FLUX 1380 lm/m EFFICIENCY 115 lm/W VOLTAGE 24 V DC INGRESS PROTECTION CODE IP44 NUMBER OF LEDS/M 192 INPUT POWER NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	COLOUR RENDERING INDEX CRI	
LUMINOUS FLUX EFFICIENCY 115 lm/W VOLTAGE 24 V DC INGRESS PROTECTION CODE NUMBER OF LEDS/M 192 INPUT POWER NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS)	RATED LIFE TIME	36.000h (L80B10), 84.000h (L70B50)
FFFICIENCY VOLTAGE 24 V DC INGRESS PROTECTION CODE IP44 NUMBER OF LEDS/M 192 INPUT POWER 24 W NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) ADDITIONAL COVER (MONTHS) 115 lm/W 24 V DC IP44 NUMBER OF LEDS/M 192 192 192 24 W 250 26 -+50°C	ENERGY EFFICIENCY CLASS	
VOLTAGE INGRESS PROTECTION CODE IP44 NUMBER OF LEDS/M INPUT POWER NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) ADDITIONAL COVER (MONTHS) 24 V DC IP44 192 24 W -20°C -+50°C	LUMINOUS FLUX	1380 lm/m
INGRESS PROTECTION CODE NUMBER OF LEDS/M 192 INPUT POWER 24 W NUMBER OF SWITCHING CYCLES AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	EFFICIENCY	115 lm/W
NUMBER OF LEDS/M INPUT POWER 24 W NUMBER OF SWITCHING CYCLES > 50 000 AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	VOLTAGE	24 V DC
INPUT POWER 24 W NUMBER OF SWITCHING CYCLES > 50 000 AMBIENT TEMPERATURE RANGE INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	INGRESS PROTECTION CODE	IP44
NUMBER OF SWITCHING CYCLES > 50 000 AMBIENT TEMPERATURE RANGE -20°C -+50°C INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	NUMBER OF LEDS/M	192
AMBIENT TEMPERATURE RANGE -20°C -+50°C INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) ADDITIONAL COVER (MONTHS) 12	INPUT POWER	24 W
INPUT POWER CONNECTOR WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	NUMBER OF SWITCHING CYCLES	> 50 000
WARRANTY PERIOD (MONTHS) 24 ADDITIONAL COVER (MONTHS) 12	AMBIENT TEMPERATURE RANGE	-20°C -+50°C
ADDITIONAL COVER (MONTHS) 12	INPUT POWER CONNECTOR	
	WARRANTY PERIOD (MONTHS)	24
INSTALLATION AND OPERATING MANUAL https://www.limente.fi/Images/productpics/instructions/limente_led-corner.pdf	ADDITIONAL COVER (MONTHS)	12
	INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-corner.pdf

Date: 19.11.2024 | Page 2 (4)



COR. 20 COM 4K BL PROF.LIGHT

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640551	SMART 551, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640552	SMART 552, LUXUS LIGHTCONTROL KIT, 24 V, WHITE
640554	SMART 554, LUXUS LIGHTCONTROL KIT, 24 V, BLACK
640556	SMART 556, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640557	SMART 557, GREENLINE LIGHTCONTROL KIT, 24 V, WHITE
640425	SMART 425, WIRELESS LIGHT CONTROL

Date: 19.11.2024 | Page 3 (4)



COR. 20 COM 4K BL PROF.LIGHT

