

PROFILE LILO

without led-strip | aluminium 2,0 m

Product code: 68913



Aluminum profile for LED strips

LIMENTE PROFILE LILO is designed for installing LIMENTE RIBBON led strip. LIMENTE LILO is designed to be used as indirect lighting and is especially pleasant when planning on illuminating via another surface. The fixture can be used e.g. in closets, when wanting to direct light toward the back wall of the closet. The profile is very small in size and, unlike other LIMENTE profiles, LILA and LILO use an 8mm led strip.

The profile has a standard length of 2 meters and can be shortened to a desired length using a hacksaw or a circular saw. When the profile is cut to a proper length, simply install the led strip inside. The profile is available in black and white. Installation tools and attachment brackets as well as end pieces are included.

[Learn more from our website](#)

Dimming and lighting control

Combine any LIMENTE RIBBON led strip with either LIMENTE SMART CLASSIC, LUXUS and GREENLINE series wireless dimming and lighting control system. With our SMART systems, you can easily change the lighting and ambience in your home from efficient and bright to dim and cozy with just a push of a button.

[Learn more from our website](#)

Installation

LIMENTE profiles are cut to a desired length using a hacksaw or a circular saw and secured in place with the supplied installation tools and attachment brackets. Please note that a led strip of max. 8mm in width is used with LIMENTE PROFILE LILO.

THE FOLLOWING ITEMS ARE INCLUDED

- aluminium profile 2m
- diffuser 2m (cover)
- mounting clips x 4
- end-caps x 4

PROFILE LILO 2M

OVERVIEW

PRODUCT CODE	68913
GTIN-CODE	6438400001909
ELECTRICAL NUMBER	4118949
ETIM GENERAL NAME	
ETIM CLASS	
ETIM GROUP	
COLOUR	
LAMP TYPE	

SPECIFICATIONS

PRODUCT DIMENSIONS	2000.0 x 22.0 x 12.5
MOUNTING METHOD	
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	
INGRESS PROTECTION CODE	
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-lilo.pdf

PROFILE LILO 2M

