## LIMENTE





#### THE FOLLOWING ITEMS ARE INCLUDED

- aluminum profile 2 m x 2
- end pieces x 8
- led-ribbon 4 m, with driver in both ends
- 3m power cords 2 pcs

#### **WALL 40**

4m | 4000 K | aluminium | 192 led/m | 1700 lm/m | CRI>90 Product code: 68923

#### An efficient wall-mounted, recessed light fixture

LIMENTE WALL IP44 LUX is a part of LIMENTE LUX collection. The LIMENTE LUX collection provides the best quality of light in technical features, such as efficiency and color rendering, and maximizes the lifespan of the product. Use WALL to bring light to table tops and stairs or sides of a wall. You're able to create safety lighting for dark hallways with WALL. You can also use WALL as indirect mood light in any room. The end result is always spectacular!

WALL is only 26mm deep allowing installation on a sheet wall without alterations to wall support structures. The led strip can be shortened to a desired length at 3,3 cm intervals, whereas the profile has a standard length of 2m and can be shortened to a desired length.

Learn more from our website

#### Dimming and lighting control

Appropriate lighting for any occasion is made easy with our dimming and lighting control system. You can easily change the lighting and ambience in your home from efficient and bright to dim and cozy by dimming your LIMENTE WALL IP44 LUX with our wireless system. You can use the same switch to adjust all the LIMENTE lights in the room, including various ceiling, panel and profile lights. The light adjusts smoothly at the same time while creating ambience for working, entertaining or any mood in between.

Learn more from our website

#### Assembly

LIMENTE WALL IP44 LUX is fast and easy to install with the installation tools included.

Learn more from our website



## WALL 40 LUX 4K AL PROF.LIGHT

#### **OVERVIEW**

PRODUCT CODE	68923
GTIN-CODE	6438400000957
ELECTRICAL NUMBER	4129666
ETIM GENERAL NAME	Light ribbon-/hose/-strip
ETIM CLASS	Light ribbon-/hose/-strip EC002706
ETIM GROUP	41 Domestic light fittings
COLOUR	Alulook
LAMP TYPE	LED

#### **SPECIFICATIONS**

PRODUCT DIMENSIONS	4000.0 x 76.2 x 26.5
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	> 90
RATED LIFE TIME	72.000h (L80B10), 120.000h (L70B50)
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	1700 lm/m
EFFICIENCY	130/135 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44
NUMBER OF LEDS/M	180
INPUT POWER	57 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	36
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_led-wall.pdf

Date: 19.02.2024 | Page 2 (4)



## WALL 40 LUX 4K AL PROF.LIGHT

#### **RECOMMENDED ACCESSORIES**

PRODUCT CODE	PRODUCT
LED28030	LIMENTE POWER SUPPLY, WHITE, 24 V, 30W, INTEGRATED CONNECTORS
LED28060	LIMENTE POWER SUPPLY, WHITE, 24 V, 60W, INTEGRATED CONNECTORS
LED28100	LIMENTE POWER SUPPLY, WHITE, 24 V, 100W, INTEGRATED CONNECTORS
640420	SMART 420, WIRELESS LIGHT CONTROL
640421	SMART 421, WIRELESS LIGHT CONTROL
640422	SMART 422, WIRELESS LIGHT CONTROL
640424	SMART 422, WIRELESS LIGHT CONTROL
640425	SMART 425, WIRELESS LIGHT CONTROL

Date: 19.02.2024 | Page 3 (4)

# LIMENTE

## WALL 40 LUX 4K AL PROF.LIGHT

