LIMENTE



872

floor socket | Shuko + RJ45 Product code: 872002

Floorsocket 872ALU

Limente floor sockets offer a stylish and timeless solution for distributing electricity, data, and antenna signals in all kinds of locations. Floor sockets are particularly convenient in car dealerships, supermarkets, stores, offices, commercial spaces, ships, and even in homes around kitchen islands. The washable and drive-over sockets are especially suitable for larger open spaces such as hypermarkets, car dealerships, cafes, and restaurant customer areas. Sockets intended for dry indoor installations are designed for offices and meeting or office spaces.

All Limente floor sockets are made with either aluminum or stainless steel frames, and their covers can be metal or the same material as the floor (carpet, wood, stone, laminate, parquet, etc.)

Learn more from our website

Socket content options

A socket can be equipped as follows (other connectors are available on special order):

Learn more from our website

Installation and Electrical Connection

The socket is installed as part of the floor by setting it into the concrete floor. For this purpose, a separately sold place holder (product number 680824) can be used, which reserves the necessary space in the casting. Once the floor is ready, the place holder is removed, and the socket is placed in its stead.

Learn more from our website

THE FOLLOWING ITEMS ARE INCLUDED

- 1 x Shuko (protected grounded 230 V socket)
- 1 x RJ45 double
- · removable hinged lid



FLOOR SOCKET 872-SR HINGED ALUMINUMLID

OVERVIEW

| PRODUCT CODE | 872002 |
|-------------------|---------------|
| GTIN-CODE | 6430022822429 |
| ELECTRICAL NUMBER | 2509118 |
| ETIM GENERAL NAME | |
| ETIM CLASS | |
| ETIM GROUP | |
| COLOUR | |
| LAMP TYPE | |

SPECIFICATIONS

| PRODUCT DIMENSIONS | 120.0 x 70.0 x 120.0 |
|-----------------------------------|---|
| MOUNTING METHOD | Flush mounting |
| COLOUR TEMPERATURE | |
| COLOUR RENDERING INDEX CRI | |
| RATED LIFE TIME | |
| ENERGY EFFICIENCY CLASS | |
| LUMINOUS FLUX | |
| EFFICIENCY | |
| VOLTAGE | 240 V |
| INGRESS PROTECTION CODE | IP65 |
| NUMBER OF LEDS/M | |
| INPUT POWER | |
| NUMBER OF SWITCHING CYCLES | |
| AMBIENT TEMPERATURE RANGE | -20°C~50°C |
| INPUT POWER CONNECTOR | |
| WARRANTY PERIOD (MONTHS) | 24 |
| ADDITIONAL COVER (MONTHS) | |
| INSTALLATION AND OPERATING MANUAL | https://www.limente.fi/Images/productpics/instructions/Limente_872_alukansi.pdf |



FLOOR SOCKET 872-SR HINGED ALUMINUMLID

RECOMMENDED ACCESSORIES

| PRODUCT CODE | PRODUCT |
|--------------|--|
| 680824 | PLACE HOLDER 872 JA 882, PLACE HOLDER 872 JA 882 |

Date: 06.04.2024 | Page 3 (4



FLOOR SOCKET 872-SR HINGED ALUMINUMLID

