


894

floor socket | 4 x Shuko

Product code: 894013



Floorsocket 894RUUVIHARJA

Limente floor sockets offer a stylish and timeless solution for distributing electricity, data, and antenna signals in all kinds of locations. Floor sockets are particularly convenient in car dealerships, supermarkets, stores, offices, commercial spaces, ships, and even in homes around kitchen islands. The washable and drive-over sockets are especially suitable for larger open spaces such as hypermarkets, car dealerships, cafes, and restaurant customer areas. Sockets intended for dry indoor installations are designed for offices and meeting or office spaces.

All Limente floor sockets are made with either aluminum or stainless steel frames, and their covers can be metal or the same material as the floor (carpet, wood, stone, laminate, parquet, etc.)

[Learn more from our website](#)

Socket content options

A socket can be equipped as follows (other connectors are available on special order):

[Learn more from our website](#)

Installation and Electrical Connection

The socket is installed as part of the floor by screwing it in place. The socket has a 200 x 200mm collar with 6 x 5mm holes for screw mounting. When installing on a raised floor, the flooring material goes on top of the collar.

[Learn more from our website](#)

THE FOLLOWING ITEMS ARE INCLUDED

- 4 x Shuko (protected grounded 230 V socket)
- detachable hinged lid with brush, screw fixing for raised floor

FLOOR SOCKET 894-SSSS SCREWFAST + BRUSHED

OVERVIEW

PRODUCT CODE	894013
GTIN-CODE	6430022823303
ELECTRICAL NUMBER	2509168
ETIM GENERAL NAME	
ETIM CLASS	
ETIM GROUP	
COLOUR	
LAMP TYPE	

SPECIFICATIONS

PRODUCT DIMENSIONS	250.0 x 90.0 x 200.0
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	240 V
INGRESS PROTECTION CODE	IP10
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/Limente_894_uppokansi.pdf

FLOOR SOCKET 894-SSSS SCREWFAST + BRUSHED

RECOMMENDED ACCESSORIES

PRODUCT CODE	PRODUCT
680825	PLACE HOLDER 892 JA 894, PLACE HOLDER 892 JA 894

FLOOR SOCKET 894-SSSS SCREWFAST + BRUSHED

