



## LIGHTNING SET LUXOR RIBDOB 3M + LUXA-31

1300 lm/m | aluminium | LUXA-31 socket

Product code: 96272

**Complete light set for kitchen workspace with completely dot-free LED strip**

The LIMENTE under-cabinet lighting set is a versatile, single product code under-cabinet lighting solution. Available in three finishes (white, black, and aluminium). The new DOB technology provides a completely dot-free light, which can be used in a profile even without a diffuser if desired.

The set offers a dual-sided light source that can be shortened to a maximum combined length of 200 cm. This lighting set provides efficient lighting controlled from the socket without the need for a separate lighting control system. The under-cabinet lighting set is available in two colour temperatures: 3000K and 4000K with a light flux of 1300 lm/m, an efficacy of 144 lm/W and the LEDs are very closely spaced (288 LEDs / meter).

### Installation and electrical connection

Installation of the LIMENTE under-cabinet lighting set is quick and easy with the installation accessories included. Specify the location where the power cord will be imported, or use an existing power cord. Specify the location where the power cord will be imported, or use an existing power cord. The power cord is plugged in from the wall. The socket is mounted at an angle against two solid, non-flammable surfaces so that its background does not remain open. The actual fastening is done with the help of the included screws. In one installation, you install both the sockets, the switch and power supply for the LED lights. See the installation instructions for more detailed instructions.

[Learn more from our website](#)

### THE FOLLOWING ITEMS ARE INCLUDED

- 2 m and 1 m aluminium profile
- diffuser 2m and 1m (cover)
- mounting clips x 6
- end-caps x 4
- 3 m 3000 K led-ribbon
- 3 m power cord in both ends
- integrated 30W driver controlled by an integrated switch

## S\_LUXOR3\_RIBDOB3K\_LUXA\_AL

## OVERVIEW

|                   |               |
|-------------------|---------------|
| PRODUCT CODE      | 96272         |
| GTIN-CODE         | 6430022826199 |
| ELECTRICAL NUMBER | 4158049       |
| ETIM GENERAL NAME |               |
| ETIM CLASS        |               |
| ETIM GROUP        |               |
| COLOUR            | Alulook       |
| LAMP TYPE         | LED           |

## SPECIFICATIONS

|                                   |                                                                                                                                                                                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT DIMENSIONS                | 3000.0 x 8.0 x 2.3                                                                                                                                                                                                  |
| MOUNTING METHOD                   |                                                                                                                                                                                                                     |
| COLOUR TEMPERATURE                | 3000 K                                                                                                                                                                                                              |
| COLOUR RENDERING INDEX CRI        | > 90                                                                                                                                                                                                                |
| RATED LIFE TIME                   | 102.000h                                                                                                                                                                                                            |
| ENERGY EFFICIENCY CLASS           |                                                                                                                                                                                                                     |
| LUMINOUS FLUX                     | 1300 lm/m                                                                                                                                                                                                           |
| EFFICIENCY                        | 144 lm/W                                                                                                                                                                                                            |
| VOLTAGE                           |                                                                                                                                                                                                                     |
| INGRESS PROTECTION CODE           | IP44/IP20                                                                                                                                                                                                           |
| NUMBER OF LEDS/M                  |                                                                                                                                                                                                                     |
| INPUT POWER                       | 27 W                                                                                                                                                                                                                |
| NUMBER OF SWITCHING CYCLES        | > 50 000                                                                                                                                                                                                            |
| AMBIENT TEMPERATURE RANGE         |                                                                                                                                                                                                                     |
| INPUT POWER CONNECTOR             |                                                                                                                                                                                                                     |
| WARRANTY PERIOD (MONTHS)          | 24                                                                                                                                                                                                                  |
| ADDITIONAL COVER (MONTHS)         |                                                                                                                                                                                                                     |
| INSTALLATION AND OPERATING MANUAL | <a href="https://www.limente.fi/Images/productpics/instructions/limente_KITLUXORDOB3M3K_KITLUXORDOB3M4K.pdf">https://www.limente.fi/Images/productpics/instructions/limente_KITLUXORDOB3M3K_KITLUXORDOB3M4K.pdf</a> |

## S\_LUXOR3\_RIBDOB3K\_LUXA\_AL

