

## KIT-PROCOM 4000K, 3M

1380 lm/m | black | SMART sensor

Product code: 96399



### Complete light set for kitchen workspace

The LIMENTE workspace light set is a versatile, shortenable light solution that can be used to create work and mood light and it is great for example as an indirect light on top of the cabinets, in recesses, plinths, ceilings, etc. in addition to kitchen work lighting. In the kitchen workspace, the profile is placed close to the front edge of the bottom of the top cabinet.

See the installation pictures for tips on how the profile can be placed in the kitchen as a working light, on top of the kitchen cabinet as indirect light or how it can be used as an indirect light for the ceiling, for example. The kitchen workspace set is available in two lengths, 3 m and 5 m with and without light control.

[Learn more from our website](#)

### Dimming and lightcontrol

By adjusting the lighting, you can customize the lighting and create lighting that suits your home and the current situation. The stepless dimmer makes it easy to create a different mood and a new look in the space. By dimming the LIMENTE luminaires, you change the lighting in your home from efficient and bright to dim and cozy. If you wish, you can use the same control to adjust all the LIMENTE luminaires in the room, including the different ceiling, panel and work luminaires. The luminaires adjust evenly and smoothly, changing the mood of the entire space.

[Learn more from our website](#)

### Easy installation

The installation of the LIMENTE workspace light is quick and easy with the included installation accessories and instructions.

[Learn more from our website](#)

#### THE FOLLOWING ITEMS ARE INCLUDED

- aluminium profile 2 + 1 m + diffuser
- mounting clips x 6
- end-caps x 4
- 3 m 4000 K led-ribbon
- 2 x 2m power cord with TOP connector
- driver 30 W
- 2-piece wireless controller
- receiver with quick connector

## KIT-PROCOM 3M 4K + DIMMER

## OVERVIEW

|                   |               |
|-------------------|---------------|
| PRODUCT CODE      | 96399         |
| GTIN-CODE         | 6430022826564 |
| ELECTRICAL NUMBER | 4158025       |
| ETIM GENERAL NAME |               |
| ETIM CLASS        |               |
| ETIM GROUP        |               |
| COLOUR            | Black         |
| LAMP TYPE         | LED           |

## SPECIFICATIONS

|                                   |                                                                                                                                                                                     |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT DIMENSIONS                | 3000.0 x 8.0 x 2.0                                                                                                                                                                  |
| MOUNTING METHOD                   |                                                                                                                                                                                     |
| COLOUR TEMPERATURE                | 4000 K                                                                                                                                                                              |
| COLOUR RENDERING INDEX CRI        | > 80                                                                                                                                                                                |
| RATED LIFE TIME                   | 102.000h                                                                                                                                                                            |
| ENERGY EFFICIENCY CLASS           |                                                                                                                                                                                     |
| LUMINOUS FLUX                     | 1380 lm/m                                                                                                                                                                           |
| EFFICIENCY                        | 144 lm/W                                                                                                                                                                            |
| VOLTAGE                           |                                                                                                                                                                                     |
| INGRESS PROTECTION CODE           | IP44/IP20                                                                                                                                                                           |
| NUMBER OF LEDS/M                  |                                                                                                                                                                                     |
| INPUT POWER                       | 28 W                                                                                                                                                                                |
| NUMBER OF SWITCHING CYCLES        | > 50 000                                                                                                                                                                            |
| AMBIENT TEMPERATURE RANGE         |                                                                                                                                                                                     |
| INPUT POWER CONNECTOR             |                                                                                                                                                                                     |
| WARRANTY PERIOD (MONTHS)          | 24                                                                                                                                                                                  |
| ADDITIONAL COVER (MONTHS)         |                                                                                                                                                                                     |
| INSTALLATION AND OPERATING MANUAL | <a href="http://www.limente.fi/Images/productpics/instructions/limente_kit_procom_smart.pdf">http://www.limente.fi/Images/productpics/instructions/limente_kit_procom_smart.pdf</a> |

## KIT-PROCOM 3M 4K + DIMMER

