



LIGHTNING SET 8MM-52 4K, 2M

1300 lm/m | aluminum | SMART sensor

Product code: 96412

Complete light set for kitchen workspace

The LIMENTE workspace light set is a versatile, shortenable light solution that can be used to create work and mood light and it is great for example as an indirect light on top of the cabinets, in recesses, plinths, ceilings, etc. in addition to kitchen work lighting. In the kitchen workspace, the profile is placed close to the front edge of the bottom of the top cabinet.

See the installation pictures for tips on how the profile can be placed in the kitchen as a working light. The kitchen workspace set is available in two lengths, 2 m and 4 m with and without light control.

[Learn more from our website](#)

Dimming and lightcontrol

By adjusting the lighting, you can customize the lighting and create lighting that suits your home and the current situation. The stepless dimmer makes it easy to create a different mood and a new look in the space. By dimming the LIMENTE luminaires, you change the lighting in your home from efficient and bright to dim and cozy. If you wish, you can use the same control to adjust all the LIMENTE luminaires in the room, including the different ceiling, panel and work luminaires. The luminaires adjust evenly and smoothly, changing the mood of the entire space.

[Learn more from our website](#)

Easy installation

The installation of the LIMENTE workspace light is quick and easy with the included installation accessories and instructions.

[Learn more from our website](#)

THE FOLLOWING ITEMS ARE INCLUDED

- aluminium profile 2 m
- diffuser 2 m (cover)
- mounting clips x 4
- end-caps x 4
- 2 m 4000 K led-ribbon
- 2 x 3m power cord with TOP connector
- driver 30 W
- 2-piece wireless controller
- receiver with quick connector

LIGHTN.SET 8MM-52 2M 4K + DIMMER

OVERVIEW

PRODUCT CODE	96412
GTIN-CODE	6430022826816
ELECTRICAL NUMBER	
ETIM GENERAL NAME	
ETIM CLASS	
ETIM GROUP	
COLOUR	Alulook
LAMP TYPE	LED

SPECIFICATIONS

PRODUCT DIMENSIONS	2000.0 x 8.0 x 2.0
MOUNTING METHOD	Surface mounting
COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	102.000h
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	1300 lm/m
EFFICIENCY	130 lm/W
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP44/IP20
NUMBER OF LEDS/M	
INPUT POWER	20 W
NUMBER OF SWITCHING CYCLES	> 50 000
AMBIENT TEMPERATURE RANGE	
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	http://www.limente.fi/Images/productpics/instructions/limente_ecol2m_ecol4m.pdf

LIGHTN.SET 8MM-52 2M 4K + DIMMER

