



## 992

floor socket | Shuko + USB A/C

Product code: 992007

### Floorsocket 992PINTASÄÄTÖ

Limente floor sockets offer a stylish and timeless solution for distributing electricity, data, and antenna signals in all kinds of locations. Floor sockets are particularly convenient in car dealerships, supermarkets, stores, offices, commercial spaces, ships, and even in homes around kitchen islands. The washable and drive-over sockets are especially suitable for larger open spaces such as hypermarkets, car dealerships, cafes, and restaurant customer areas. Sockets intended for dry indoor installations are designed for offices and meeting or office spaces.

All Limente floor sockets are made with either aluminum or stainless steel frames, and their covers can be metal or the same material as the floor (carpet, wood, stone, laminate, parquet, etc.)

[Learn more from our website](#)

### Socket content options

A socket can be equipped as follows (other connectors are available on special order):

[Learn more from our website](#)

### Installation and Electrical Connection

The socket is installed as part of the floor by embedding it into the concrete floor. For this purpose, a separately sold place holder (product number 680822) can be used, which reserves the necessary space during casting. Once the floor is ready, the place holder is removed, and the socket is placed in its place.

[Learn more from our website](#)

### THE FOLLOWING ITEMS ARE INCLUDED

- 1 x Shuko (protected grounded 230 V socket)
- 1 x USB A/C
- round floorsocket, installation plate for gluing the floor surface

## FLOOR SOCKET 992-SU SURFACE FLOOR + ADJUSTMENT FOOT

## OVERVIEW

PRODUCT CODE	992007
GTIN-CODE	6430022823464
ELECTRICAL NUMBER	2509178
ETIM GENERAL NAME	
ETIM CLASS	
ETIM GROUP	
COLOUR	
LAMP TYPE	

## SPECIFICATIONS

PRODUCT DIMENSIONS	150.0 x 150.0 x 80.0
MOUNTING METHOD	Flush mounting
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	240 V
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	-20°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	<a href="https://www.limente.fi/Images/productpics/instructions/Limente_992_pintakansi.pdf">https://www.limente.fi/Images/productpics/instructions/Limente_992_pintakansi.pdf</a>

## FLOOR SOCKET 992-SU SURFACE FLOOR + ADJUSTMENT FOOT

### RECOMMENDED ACCESSORIES

**PRODUCT CODE**

**PRODUCT**

680822

PLACE HOLDER 992, PLACE HOLDER 992

## FLOOR SOCKET 992-SU SURFACE FLOOR + ADJUSTMENT FOOT

