

LED DALI POWER SUPPLY

white | 24 V | 0-100 W | IP20

Product code: LEDDALI100



24 V Dali driver for LED light fixtures

LIMENTE 24V DALI power supplies are designed to work with 24V LIMENTE lights. The power supply is as small as possible, making them easy to hide in for example furniture. The DALI power supplies have fixed screw terminals on the primary side for connecting the input and DALI signal. On the secondary side, there is at the end of a cord a 6-way distributor for LED lights. In addition, the power supply has versatile protections in case of various fault situations.

LIMENTE 24V lights, which you can recognize by the black connectors, can be directly connected to the 24V DALI power supply with fast connectors.

Dimming and lighting control

By adjusting the lighting, you can always customize the lighting and create lighting that suits your home in any situation. By dimming LIMENTE lights, you can change the home lighting from efficient and bright to dim and cozy. The lights adjust evenly and at the same time, changing the atmosphere of the entire space at once.

[Learn more from our website](#)

Protection

DALI power supplies are protected against various fault situations. At the same time, the protection extends the life of the product. The protections used are:

[Learn more from our website](#)

THE FOLLOWING ITEMS ARE INCLUDED

- 100W DALI-2.0 DT6 driver
- six L806 female connectors at the end of a fixed 176mm cable (2 x 0.75mm²) for LED lights

DALI 24V DRIVER 100W IP20

OVERVIEW

PRODUCT CODE	LEDDALI100
GTIN-CODE	6430022821729
ELECTRICAL NUMBER	4009752
ETIM GENERAL NAME	Transformer
ETIM CLASS	LED driver EC002710
ETIM GROUP	40 Lighting components
COLOUR	
LAMP TYPE	

SPECIFICATIONS

PRODUCT DIMENSIONS	336.6 x 30.0 x 19.0
MOUNTING METHOD	Surface mounting, Cable coupling
COLOUR TEMPERATURE	
COLOUR RENDERING INDEX CRI	
RATED LIFE TIME	
ENERGY EFFICIENCY CLASS	
LUMINOUS FLUX	
EFFICIENCY	
VOLTAGE	24 V DC
INGRESS PROTECTION CODE	IP20
NUMBER OF LEDS/M	
INPUT POWER	
NUMBER OF SWITCHING CYCLES	
AMBIENT TEMPERATURE RANGE	-40°C~50°C
INPUT POWER CONNECTOR	
WARRANTY PERIOD (MONTHS)	24
ADDITIONAL COVER (MONTHS)	
INSTALLATION AND OPERATING MANUAL	https://www.limente.fi/Images/productpics/instructions/limente_leddali100.pdf

DALI 24V DRIVER 100W IP20

